INFORMATION PRESENTATION APPARATUS AND INFORMATION PROCESSING METHOD THEREOF

BACKGROUND OF THE INVENTION

5   Field of the Invention

The present invention relates to an information presentation apparatus which presents an image obtained by synthesizing (or composing) a real world and a virtual world, and an image processing method

10   of the information presentation apparatus.

Related Background Art

Recently, an apparatus to which a mixed reality (MR) technique of naturally combining a real world and a virtual world with each other without

15   uncomfortableness is applied is actively proposed. Among them, an apparatus which superposes virtual information on the real world and/or the virtual world observed by a user wearing a head mounted display (HMD), and presents the obtained information

20   to the user is proposed, whereby it is expected in this apparatus to improve working properties concerning engineering work, maintenance and the like. For example, a method of supporting a surveying work by superposing virtual flags on the image of the real

25   world and then displaying the obtained image on the user's HMD is proposed. However, many of these apparatuses are premised on use of only a single user,

whereby it is difficult to say that these apparatuses are suitable for the working in which conference, lecture, cooperation or the like that shares a single mixed reality (MR) space with plural persons is

5 necessary.

In other words, in the case where the plural persons perform the conference, the lecture or the like by sharing the single MR space, it is necessary for these persons to observe the same target and thus

10 share the information concerning the target in question.

SUMMARY OF THE INVENTION

An object of the present invention is to be able

15 to provide predetermined information to users, by superposing an annotation on an image obtained by synthesizing a real world and a virtual world.

For example, the present invention aims to provide a means for transmitting a target that one

20 user wishes to cause another user to pay attention, a means for knowing position and direction of a target that users should pay attention, or a means for knowing whether or not a target that one user is paying attention at present is observed by another

25 user.

In order to achieve the above object, the present invention is characterized by an information

presentation apparatus comprising:

a user operation input unit, adapted to input an operation of a user;

a user viewpoint position and pose measurement unit, adapted to measure a position and pose at a user's viewpoint;

a model data storage unit, adapted to store virtual world model data, real world model data, and data necessary to generate a virtual world image;

an annotation data storage unit, adapted to store data necessary to be added to a real world and a virtual world and then displayed;

a virtual image generation unit, adapted to generate an image of the virtual world by using information in the user viewpoint position and pose measurement unit, the model data storage unit and the annotation data storage unit;

a user viewpoint image input unit, adapted to capture an image of the real world viewed from the user's viewpoint; and

an image display unit, adapted to display an image obtained by synthesizing the image generated by the virtual image generation unit and the image obtained by the user viewpoint image input unit, on an image display device of the user.

Moreover, to achieve the above object, the present invention is characterized by an information

processing method comprising the steps of:

inputting viewpoint information of a user;

generating a virtual world image according to
the viewpoint information, by using previously held
virtual world data;

generating an annotation concerning an attention
target; and

generating an image obtained by synthesizing an
image of a real world, generated virtual world image
and the generated annotation.

Moreover, to achieve the above object, the
present invention is characterized by a program to
achieve an information processing method comprising
the steps of:

inputting viewpoint information of a user;

generating a virtual world image according to
the viewpoint information, by using previously held
virtual world data;

generating an annotation concerning an attention
target; and

generating an image obtained by synthesizing an
image of a real world, generated virtual world image
and the generated annotation.

Other objects and features of the present
invention will become apparent from the following
description taken in conjunction with the
accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram schematically showing the structure of an information presentation apparatus according to the embodiment;

Fig. 2 is a block diagram showing the structure in a case where plural information presentation apparatuses are mutually connected together through a transmission channel, according to the embodiment;

Fig. 3 is a flow chart for explaining a process procedure in the information presentation apparatus;

Fig. 4 is a diagram for explaining a means which informs, in a case where a target that a watching user pays attention is outside a visual range of a watched user, the watched user of the position of the target, according to the embodiment;

Fig. 5 is a diagram for explaining a means which informs, in a case where the target that the watching user pays attention is inside the visual range of the watched user, the watched user of the target and information concerning the target, according to the embodiment;

Fig. 6 is a diagram for explaining a means which presents to the watching user whether or not the target that the watching user pays attention is inside the visual range of each watched user, according to the embodiment; and

Fig. 7 is a diagram for explaining a means which

presents to a user positions where other users exit, according to the embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5   Hereinafter, the embodiments of the present invention will be described with reference to the accompanying drawings.
(One Embodiment)

        Fig. 1 is a block diagram schematically showing
10   the entire structure to which an information presentation apparatus and an information presentation method according to the embodiment are applied.

        A user operation input unit 101 is an input
15   device which consists of, e.g., push button switches, a mouse, a joystick and the like. When a user of an information presentation apparatus 100 operates or handles the user operation input unit 101, control information according to operation contents by the
20   user is transferred to a virtual image generation unit 105.

        A user viewpoint position and pose measurement unit 102 is a position and pose measurement device such as a magnetic sensor, an optical sensor or the
25   like. The user viewpoint position and pose measurement unit 102 measures a position and pose at a user's viewpoint by six degrees of freedom and

transfers a measured result to the virtual image
generation unit 105. Since it is generally difficult
to set the position and pose measurement device at
the user's viewpoint, the user viewpoint position and
pose measurement unit 102 has a function to calculate
the position and pose at the user's viewpoint on the
basis of the output result of the position and pose
measurement device. For example, in a case where the
position and pose measurement device is fixed to a
user's head, a relation between the output of the
position and pose measurement device and the position
and pose at the user's viewpoint is always maintained
constant, whereby the relation is expressed by a
certain expression. Therefore, by obtaining the
certain expression in advance, the position and pose
at the user's viewpoint is calculated based on the
output from the position and pose measurement device.
Besides, it is possible to capture an image of a real
world by using a user viewpoint image input unit 106,
and thus perform an image process of the captured
image to correct an error in the output result of the
position posse measurement device. In the image
process, for example, positions of plural feature
points of which the three-dimensional coordinates in
a real space have been known are detected from the
image, the detected positions are compared with the
positions of feature points of the image calculated

from the output result of the position and pose
measurement device to calculate the error in the
output result of the position posse measurement
device, and the output result of the position and
5   pose measurement device is corrected so as to delete
the calculated error. Moreover, it is possible to
calculate the position and pose at the user's
viewpoint only from the image process.

     A model data storage unit 103 is an auxiliary
10   storage device or medium such as a hard disk, a CD-
ROM or the like. The model data storage unit 103
holds and stores virtual world model data necessary
to draw a virtual world by computer graphics (CG),
real world model data necessary to accurately
15   synthesize the real world and the virtual world, and
data necessary to generate a virtual world image.
Here, the virtual world model data includes three-
dimensional coordinates of vertices of a polygon of a
virtual CG object arranged on the virtual world,
20   structure information of faces of the polygon,
discrimination information of the CG object, color
information of the CG object, texture information of
the CG object, size information of the CG object,
position and pose information indicating the
25   arrangement of the CG object in the virtual world,
and the like. The real world model data includes
three-dimensional coordinates of vertices of a

polygon of an object existing in the real world
merged with the virtual world, structure information
of faces of the polygon, discrimination information
of the object, size information of the object,

5   position and pose information indicating the
arrangement of the object, and the like. The data
necessary to generate the virtual world image
includes size and angle of an image pickup element of
an image pickup device of the user viewpoint image

10   input unit 106, and internal parameters such as an
angle of view of a lens, a lens distortion parameter
and the like. The information stored in the model
data storage unit 103 is transferred to the virtual
image generation unit 105. Here, the model data

15   storage unit 103 is not limited to that provided
inside the information presentation apparatus 100,
that is, the model data storage unit 103 may be
provided outside the information presentation
apparatus 100 so as to transfer the data to the

20   virtual image generation unit 105 through a
transmission channel 200.

An annotation data storage unit 104 is an
auxiliary storage device or medium such as a hard
disk, a CD-ROM or the like. The annotation data

25   storage unit 104 holds and stores annotation data
which indicates additional information to be
displayed on the real world and the virtual world.

The annotation data includes position and pose information of the object in the real world and the virtual world, discrimination information of the object, and text, symbol and image information for indicating the object to a user. Here, the annotation data storage unit 104 is not limited to that provided inside the information presentation apparatus 100, that is, the annotation data storage unit 104 may be provided outside the information presentation apparatus 100 so as to transfer the data to the virtual image generation unit 105 through the transmission channel 200.

The virtual image generation unit 105 is actualized by a CPU, a microprocessor unit (MPU) or the like mounted in a computer. On the basis of position and pose information indicating the position and pose at the user's viewpoint obtained from the user viewpoint position and pose measurement unit 102, the virtual image generation unit 105 sets the user's viewpoint in the virtual world, draws the model data stored in the model data storage unit 103 by the CG from the set viewpoint, and thus generates the image of the virtual world viewed from the user's viewpoint. Moreover, as shown in Fig. 2, the virtual image generation unit 105 which has a function to transmit the data to the transmission channel 200 and receive the data from the transmission channel 200 is

connected mutually to a virtual image generation unit
105 of another information presentation apparatus 100
through the transmission channel 200 so as to
exchange necessary information between them. Thus,
5   plural users use the respective information
presentation apparatuses 100, whereby they can share
the same (or identical) MR space. Fig. 2 is the block
diagram showing the structure in the case where the
plural information presentation apparatuses 100
10   mutually connected together through the transmission
channel 200 are used by the plural users. In
accordance with the position and pose at the user's
viewpoint obtained from the user viewpoint position
and pose measurement unit 102 and the position and
15   pose of other user's viewpoint obtained through the
transmission channel 200, the virtual image
generation unit 105 generates an annotation to be
presented to the user, on the basis of the annotation
data stored in the annotation data storage unit 104.
20   Then, the virtual image generation unit 105
superposes the generated annotation on the image of
the virtual world, and further displays the obtained
image. Here, the generated annotation is not limited
to a two-dimensional annotation. That is, the virtual
25   image generation unit 105 may generate a three-
dimensional annotation and draw the generated
annotation by the CG together with the virtual world

model stored in the model data storage unit 103.
Incidentally, the virtual image generation unit 105
has a function to operate the virtual world and
control the generated annotation according to user's
5 operation information transferred from the user
operation input unit 101.

The user viewpoint image input unit 106 which
includes one or two image pickup devices such as a
CCD camera or the like captures an image of the real
10 world which greets user's eyes and then transfers the
captured image to an image display unit 107. Here, in
a case where the image display unit 107 is equipped
with an optical see-through HMD, the user can
directly observe the real world, whereby the user
15 viewpoint image input unit 106 is unnecessary in this
case.

The image display unit 107 includes an image
display device such as the HMD, a display or the like.
The image display unit 107 synthesizes the image of
20 the real world greeting the user's eyes and captured
by the user viewpoint image input unit 106 and the
image of the virtual world generated by the virtual
image generation unit 105 together and then displays
the synthesized image right in front of the user's
25 eyes. Here, in the case where the image display unit
107 is equipped with the optical see-through HMD, the
image of the virtual world generated by the virtual

image generation unit 105 is displayed right in front of the user's eyes. Here, it should be noted that the image display unit 107 also acts as an image drawing unit according to an operation.

5   The transmission channel 200 is a medium which achieves a wired or wireless computer network. The plural information presentation apparatuses 100 are connected to the transmission channel 200, whereby the data to be mutually exchanged among the

10   information presentation apparatuses 100 flows in the transmission channel 200.

      Hereinafter, control of the embodiment in which the above structure is provided will be explained. Fig. 3 is a flow chart for explaining a process

15   procedure in the information presentation apparatus according to the embodiment.

      In a step S000, the information presentation apparatus is activated, and a process necessary for initialization is performed.

20   In a step S100, the user's operation to the user operation input unit 101 is recognized and converted into a control signal according to the operation content, and the obtained control signal is transferred to the virtual image generation unit 105.

25   In a step S200, the position and pose information indicating the position and pose at the user's viewpoint is measured by the user viewpoint

position and pose measurement unit 102, and the obtained information is transferred to the virtual image generation unit 105.

In a step S300, the image of the real world viewed from the user's viewpoint is captured by the user viewpoint image input unit 106, and the captured image is then transferred to the image display unit 107. Here, in the case where the image display unit 107 is equipped with the optical see-through HMD as the display, the user can directly observe the real world, whereby the process in the step S200 is unnecessary.

In a step S400, communication data is received by the virtual image generation unit 105 through the transmission channel 200. For example, the communication data includes identification number information of each user using the information presentation apparatus 100, name information capable of discriminating each user, position and pose information of each user's viewpoint, operation information of each user, the annotation data and the like.

In a step S500, the annotation to be presented to the user is determined by the virtual image generation unit 105 on the basis of the user's operation information obtained in the step S100, the position and pose information at the user's viewpoint

obtained in the step S200, and the information concerning other user obtained in the step S400.

In the step S500, when a target in the real world or the virtual world that one user pays attention is notified to other users so that the other users pay attention to it, the plural users resultingly share the information in the MR space, whereby it is very useful for the plural users to perform working in which conference, lecture, cooperation or the like is necessary. Hereinafter, a means to achieve such an effect will be explained.

First, the data concerning the target that the user pays attention at present is retrieved and selected from the information of the objects in the real world and the virtual world stored in the annotation data storage unit 104. Incidentally, the target that the user pays attention may be automatically recognized and selected by the information presentation apparatus 100 or manually selected according to the user's operation on the user operation input unit 101.

In the method of automatically recognizing the target that the user pays attention, it is thought to use the position and pose information indicating the position and pose at the user's viewpoint obtained in the step S200 and the internal parameters of the image pickup device held in the model data storage

unit 103.

Incidentally, in the step S500, all candidates of the targets existing inside the user's visual range are captured from the annotation data storage unit 104 on the basis of the internal parameters of the image pickup device and the position and pose information indicating the position and pose at the user's viewpoint. Then, in regard to the captures candidate, a Euclidean distance between a user's visual line and a point representative of the target is calculated, and the candidate for which the Euclidean distance is minimum can be considered as an attention target.

In case of judging whether or not one target is within the user's visual range, for example, it is thought to do so by the calculation from the position and pose information indicating the position and pose at the user's viewpoint obtained from the user viewpoint position and pose measurement unit 102 and the internal parameters of the image pickup device provided in the user viewpoint image input unit 106. That is, the target is projected on an image screen from the position and pose at the user's viewpoint by using the internal parameters of the image pickup device. Then, when the coordinates of the target projected on the image screen exist within a certain range defined by the size of the image, it is judged

that the target in question is within the user's
visual range.

It is assumed that a matrix created from the
internal parameters of the image pickup device is

5   given as follows.

$$
K = \begin{pmatrix} \alpha_u & -\alpha_u \cot\theta & u_0 \\ 0 & \alpha_v/\sin\theta & v_0 \\ 0 & 0 & 1 \end{pmatrix}
$$

where each of the symbols α_u and α_v indicates a pixel

10 size of the image pickup device, the symbol θ
indicates an angle between the longitudinal and
lateral axes of the image pickup element, and the
symbols u_0 and v_0 indicate coordinates of the pixel
center. Moreover, it is assumed that a matrix created

15 from the position and pose at the user's viewpoint is
P = (Rt), where the symbol R indicates a rotation
matrix of three rows and three columns representing
the pose at the user's viewpoint, and the symbol t
indicates a three-dimensional vector of the position

20 of the user's viewpoint. Besides, it is assumed that
the three-dimensional coordinates of the target are
given as $x = (X, Y, Z, 1)^T$ by using the expression of
the homogeneous coordinates, and the coordinates of
the point of the target projected on the image screen

25 are given as $u = (u, v, w)^T$ by using the expression of
the homogeneous coordinates.

The coordinates u of the point of the target

projected on the image screen can be obtained by calculation of $u = KP^{-1}x$. Then, when it is assumed that a range of the image in the u-axis direction is $[u_{min}, u_{max}]$ and a range of the image in the v-axis direction is $[v_{min}, v_{max}]$, if $u_{min} \leq u \leq u_{max}$ and $v_{min} \leq v \leq v_{max}$ are satisfied, it can be known that the target in question is within the user's visual range.

To calculate a distance between a straight line obtained from the position and pose at the user's viewpoint and the point representative of the target, it is thought to obtain the vector which passes the point representative of the target and crosses the user's visual line and then calculate the minimum value of the length of the vector in question.

The user's visual line is expressed as $v = t + kp$, where the symbol t indicates the three-dimensional vector of the position of the user's viewpoint, the symbol p indicates a three-dimensional vector of the pose at the user's viewpoint, and the symbol k is a real number other than "0."

Moreover, the point representative of the target is expressed by a three-dimensional vector b. Then, when it is assumed that the point where the vector passing the three-dimensional vector b and orthogonal to the visual line crosses the visual line is given as $t + mp$, the value m which minimizes the distance between the point $t + mp$ and the three-dimensional

vector b may be obtained. That is, $\|t + mp - b\|$ is the distance between the visual line and the point representative of the target.

When this distance is calculated, $\|t - b + (p \cdot (b$

5 $- t)/\|b\|^2)p\|$ is obtained.

Incidentally, as a method of selecting the target that the user pays attention by handling and operating the input device of the user operation input unit 101, it is thought that the watching user

10 operates the input device by using the mouse or the joystick as watching the synthesized image displayed on the image display unit 107. For example, the user handles and moves the mouse to the position where the attention target is being displayed, and then

15 depresses the button of the mouse at that position, thereby selecting the desired target. Then, when the cursor handled by the user reaches the position where the object stored in the annotation data storage unit 104 is being displayed, the user can confirm whether

20 or not the data concerning the object is being stored in the annotation data storage unit 104 by generating the annotation concerning the object.

An identification number of the target that the user pays attention is transferred to the

25 transmission channel 200 in a step S600. At the same time, also a user identification number and the position and pose information are transferred to the

transmission channel 200. Moreover, in the step S400, the identification number information of the target that another user pays attention, the another user's identification number and the position and pose

5   information are received from the transmission channel 200.

In the virtual image generation unit 105 of the information presentation apparatus 100 which is used by one user (called a watched user hereinafter), when

10   it is judged that the target that another user (called a watching user hereinafter) pays attention is outside the visual range of the watched user, the annotation indicating the direction of the target is generated. This annotation includes symbols,

15   characters, images and the like. To enable to easily recognize the target that which watching user is paying attention, it is possible to generate an annotation of which the attributes such as a color, a shape, a character type and the like have been

20   changed in regard to each watching user, or an annotation which indicates a name capable of discriminating the watching user. Thus, when the watched user turns toward the direction indicated by the annotation, he can watch the target that the

25   watching user is observing.

When the target that the watching user is paying attention is inside the visual range of the watched

user, the annotation indicating the information of the target in question is generated. At that time, the attributes of the generated annotation such as the color, the shape, the character type and the like are made different from those of other annotation so as to make the generated annotation remarkable.

Moreover, when the watched user uses the input device of the user operation input unit 101, he can control the target of the generated annotation. For example, it is possible to select the specific watching user and then generate only the annotation concerning the target that the selected specific watching user pays attention. On the contrary, it is possible to generate the annotation concerning the target that all the watching users pay attention. In this case, such a selection is performed not only by the watched user's operation with use of the input device but also by the previous input before the step S000.

Fig. 4 shows a situation that, in a case where a user 1 being the watching user observes a certain building and the building is outside the visual range of a user 2 being the watched user, the arrow indicating the direction of the building and the annotation indicating the name of the user 1 are generated and displayed on the screen to be presented to the user 2.

Fig. 5 shows a situation that, in a case where
the user 1 being the watching user is paying
attention to the certain building and the building is
inside the visual range of the user 2 being the
5   watched user, the annotation (black background and
white text) indicating the name of the building is
generated and displayed on the screen to be presented
to the user 2. In this situation, the attributes
(black background and white text) of the generated
10   annotation are made different from the attributes
(white background and black text) of another
annotation, so as to make the generated annotation
remarkable.

In the information presentation apparatus 100
15   which is used by the watching user, in case of
generating the annotation of the information
concerning the attention target, the attributes
(color, shape, character type, etc.) of the
annotation to be generated are made different from
20   those of other annotations so as to make the
annotation to be generated remarkable. Moreover, the
annotation of the information indicating whether or
not the attention target is being observed by the
watched user is generated and presented to the
25   watching user.

Fig. 6 shows a situation that the user 1 being
the watching user is paying attention to the certain

building, and the annotation (black background and white text) indicating the name of the building is generated and made to have the attributes different from those of other annotations so as to make the

5   generated annotation remarkable. Moreover, Fig. 6 shows a situation that the annotation of the information indicating whether or not the watched users are paying attention to the building is generated and displayed.

10   Moreover, in the information presentation apparatus 100 of each user, in a case where another user exists inside the visual range of the user in the real world, the annotation indicating the name capable of discriminating that (another) user is

15   generated. On the contrary, in a case where another user does not exist inside the visual range of the user in the real world, the annotation including the arrow indicating the direction of each user and the name capable of discriminating that user is generated.

20   Fig. 7 shows a situation that the annotation indicating the position of a user 4 existing inside the visual range of the user 1 is generated and displayed on the image screen of the user 1, and the annotation including the arrow indicating the

25   direction of the users 2 and 3 existing outside the visual range of the user 1 and the names capable of discriminating these users is generated and displayed

on the image screen of the user 1.

In the step S600, the communication data is transferred from the virtual image generation unit 105 to the transmission channel 200. For example, the communication data includes the identification number information of each user using the information presentation apparatus 100, the name information capable of discriminating each user, the position and pose information of each user's viewpoint, the operation information of each user, the annotation data and the like.

In a step S700, in accordance with the model data stored in the model data storage unit 103, the user's viewpoint is set based on the position and pose information at the user's viewpoint obtained in the step S200, and the virtual world which can be viewed from that viewpoint is drawn. Moreover, the annotation determined in the step S600 is superposed and drawn on the image of the virtual world.

In the step S700, the image of the real world viewed from the user's viewpoint position and obtained in the step S200 may be first drawn as the background, and the virtual world and the annotation may be then superposed and drawn on the background. At that time, in a step S800, a process of only outputting the image obtained as the result of the drawing to the image display device.

In the step S800, the image of the real world
viewed from the user's viewpoint position and
obtained in the step S200 and the image of the
virtual world generated in the step S700 are
5   synthesized, and then the synthesized image is drawn
and output to the image display device. Here, in the
case where the image display device of the image
display unit 107 is equipped with the optical see-
through HMD, the image of the virtual world is drawn
10   and output to the image display device.

In a step S900, it is judged whether or not to
end the operation of the information presentation
apparatus 100. When it is judged not to end the
operation, then the flow returns to the step S100,
15   while when it is judged to end the operation, the
process ends as a whole.

According to the embodiment, it is possible to
notify other user of the target that one user wishes
to cause the other user to pay attention, it is
20   possible for the user to know the position and the
direction of the target that the user should pay
attention, and it is further possible to know whether
or not the target that one user is paying attention
at present is observed by other user. Therefore, it
25   is easy to perform the working in which the
conference, the lecture, the cooperation or the like
that shares the single mixed reality space with the

plural persons is necessary.

(Other Embodiment)

The object of the present invention can be achieved even in a case where a storage medium (or a recording medium) storing therein program codes of software to realize the functions of the above embodiment is supplied to a system or an apparatus, and thus a computer (or CPU, MPU) in the system or the apparatus reads and executes the program codes stored in the storage medium. In this case, the program codes themselves read from the storage medium realize the functions of the above embodiment, whereby the storage medium storing these program codes constitutes the present invention. Moreover, it is needless to say that the present invention includes not only a case where the functions of the above embodiment are realized by executing the program codes read by the computer, but also a case where an operating system (OS) or the like running on the computer performs a part or all of the actual processes on the basis of instructions of the program codes and thus the functions of the above embodiment are realized by such processes.

Moreover, it is needless to say that the present invention also includes a case where, after the program codes read from the storage medium are written into a function expansion card inserted in

the computer or a memory in a function expansion unit connected to the computer, a CPU or the like provided in the function expansion card or the function expansion unit performs a part or all of the actual

5   processes on the basis of the instructions of the program codes, and thus the functions of the above embodiments are realized by such processes.

As many apparently widely different embodiments of the present invention can be made without

10   departing from the spirit and scope thereof, it is to be understood that the present invention is not limited to the specific embodiments thereof expect as defined in the appended claims.